

Medswap 22"

Panel PC with swappable batteries

Powered by a high-performance Intel® Core i5 or i7 processor, the Medswap ensures uninterrupted operation thanks to its hot-swappable batteries. Its specific features make it ideal for use in environments requiring strict hygiene standards.



FEATURES



Intel Core i5 or i7 processor



3 Li-ion batteries - 12.4 V
8 to 16 hours of battery life



22" multi-layer projected capacitive technology and wide viewing angles



Special IP65 antimicrobial coating



CE Medical



Adapts to all types of supports :
treatment trolleys, wall mounts, arms,
medical stands

AVAILABLE OPTIONS



6-slot charging
station



CE Medical Mains
Adapter



Desk mount
bracket



TECHNICAL SPECIFICATIONS

Screen	21.5" Touchscreen 1920 x 1080
Processor	Intel® Core™ Ultra 5 processor 14th generation Intel® Core™ Ultra 7 processor 14th generation
Operating system	Windows 10 or 11
Storage	256 GB to 4 TB SSD
RAM	from 8 GB to 64 GB
Network interface	Ethernet 10/100/1000 MB Base-T LAN; Wi-Fi 802.11ax, 2.4/5 GHz Dual Band
Batteries	swappable Li-Ion batteries 8250mAh, 90Wh
I/O Ports	4 x USB 3.0, 2 x USB 2.0, 1 HDMI (1.4a), 2 ports COM RS232, 1x RJ45, 1 x audio jack (3,5mm), 1 DC jack in, DC out 1x12V,1x15V (option), 1x 19V
Power supply	Input: 100 – 240V AC; Output: 19V DC, 6.31A
Dimensions	13.6 x 20.4 x 1.6 in/345.9 x 516.9 x 40.4 mm
Weight	5,7 kg (without batterie) ; 7,2 kg (with 3 batteries)
Material	ABS + Plastic with antimicrobial coating
Mount	VESA 100 x 100 mm (75 x 75 mm adapter available)
Certifications	ANSI/AAMI ES60601-1, IEC60601-1, IEC60601-1-2, FCC Part 18, FCC Part 15 Class B, GB 17625.1, GB 4943.1, GB/T 9254, CE-EMC, CE-RED, Energy Star 8.0, RCM, CCC
Operating temperatures	Operating : 0°C ~ 40°C (32°F ~ 104°F); Storage: -20°C ~ 60°C (-4°F ~ 140°F)
Humidity	0% - 90 %
Availables options	NFC/RFID reader CAC/Smart Card reader 5 MP camera

Designers of mobile computing solutions for hospitals and clinics



www.mediantech.fr



info@mediantech.fr



05 34 59 86 45

